

DYNOMite Test Run: MRL 383 BBM #14 on 2015-02-13 @ 11-38-02

Date: 2/13/2015

Correction Method: Standard

400

Sec (Seconds)	RPM (RPM)	Torque (ft-lb)	Hp (Hp)	A/F (A/F)	O2 (A/F)	BSFC (lb/Hp-hr)	PSI-7 B1 (PSI)
0.000	3349	429.0	273.5	11.38	11.93	0.512	7.385
0.100	3361	430.2	275.2	11.40	11.92	0.509	7.386
0.200	3377	431.5	277.5	11.42	11.91	0.505	7.389
0.300	3400	433.4	280.5	11.45	11.91	0.502	7.390
0.400	3430	435.8	284.6	11.48	11.91	0.497	7.391
0.500	3470	439.1	290.1	11.53	11.93	0.491	7.389
0.600	3520	443.1	297.0	11.62	11.98	0.482	7.387
0.700	3579	447.5	304.9	11.76	12.06	0.472	7.385
0.800	3643	452.2	313.6	11.93	12.16	0.461	7.383
0.900	3709	456.5	322.4	12.10	12.26	0.452	7.378
1.000	3774	460.2	330.7	12.24	12.33	0.445	7.372
1.100	3833	462.9	337.8	12.31	12.38	0.441	7.361
1.200	3885	464.5	343.6	12.31	12.42	0.441	7.346
1.300	3929	465.3	348.1	12.30	12.47	0.443	7.329
1.400	3966	465.8	351.7	12.29	12.51	0.445	7.311
1.500	3998	466.2	354.9	12.31	12.56	0.445	7.296
1.600	4027	466.6	357.8	12.34	12.60	0.444	7.285
1.700	4054	466.9	360.4	12.37	12.64	0.444	7.279
1.800	4082	467.1	363.0	12.39	12.67	0.444	7.276
1.900	4110	467.0	365.4	12.39	12.71	0.444	7.274
2.000	4138	466.8	367.8	12.38	12.76	0.444	7.270
2.100	4167	466.7	370.2	12.39	12.81	0.444	7.265
2.200	4196	466.5	372.6	12.40	12.85	0.444	7.259
2.300	4225	466.3	375.1	12.41	12.88	0.444	7.252
2.400	4254	466.0	377.5	12.42	12.90	0.444	7.246
2.500	4284	465.8	379.9	12.41	12.91	0.444	7.240
2.600	4315	465.6	382.5	12.42	12.92	0.444	7.235
2.700	4347	465.5	385.3	12.43	12.93	0.444	7.229
2.800	4380	465.7	388.4	12.44	12.93	0.443	7.225
2.900	4417	465.8	391.7	12.43	12.95	0.444	7.223
3.000	4456	465.8	395.2	12.42	12.97	0.444	7.227
3.100	4497	465.6	398.7	12.40	13.01	0.445	7.233
3.200	4540	465.1	402.0	12.38	13.05	0.446	7.239
3.300	4582	464.4	405.1	12.38	13.08	0.446	7.241
3.400	4622	463.4	407.8	12.40	13.09	0.446	7.239
3.500	4660	462.5	410.4	12.48	13.06	0.444	7.236
3.600	4696	462.0	413.1	12.58	13.02	0.441	7.232
3.700	4732	461.8	416.1	12.70	12.98	0.437	7.230
3.800	4768	461.5	419.0	12.81	12.97	0.434	7.226
3.900	4805	460.8	421.6	12.88	12.98	0.433	7.223
4.000	4840	459.5	423.5	12.91	13.02	0.433	7.221
4.100	4874	457.8	424.8	12.92	13.05	0.435	7.220
4.200	4907	455.9	426.0	12.93	13.07	0.436	7.219
4.300	4939	454.4	427.3	12.96	13.07	0.436	7.215
4.400	4972	453.0	428.9	12.99	13.06	0.436	7.208
4.500	5005	451.8	430.6	13.00	13.09	0.436	7.200
4.600	5038	450.6	432.3	12.99	13.14	0.436	7.193
4.700	5073	449.2	433.9	12.96	13.20	0.437	7.186
4.800	5108	447.4	435.2	12.91	13.24	0.439	7.180
4.900	5143	445.2	436.0	12.90	13.22	0.440	7.175
5.000	5178	442.6	436.3	12.88	13.18	0.441	7.171
5.100	5213	439.6	436.3	12.85	13.11	0.443	7.170
5.200	5247	436.0	435.6	12.83	13.05	0.445	7.172
5.300	5278	432.0	434.1	12.80	13.03	0.449	7.173

467-436