

DYNomite Test Run: MRL 440 Street on 2012-03-14 @ 16-45-44

Date: 3/14/2012

Correction Method: Standard

Notes: Primed 66 lbs w drill

Sec (Seconds)	RPM (RPM)	Torque (ft-lb)	Hp (Hp)	0-5v2 B1 (Volts)	E-Temp (Degree F)	PSI-4 B1 (PSI)
0.000	3193	501.3	304.8	12.70	170	66.64
0.100	3195	501.5	305.1	12.67	170	66.64
0.200	3201	502.0	305.9	12.61	170	66.65
0.300	3210	501.9	306.7	12.57	170	66.66
0.400	3224	501.4	307.7	12.52	170	66.68
0.500	3246	500.3	309.2	12.46	170	66.72
0.600	3276	498.7	311.0	12.37	170	66.78
0.700	3313	497.2	313.7	12.22	170	66.86
0.800	3359	496.9	317.8	12.06	170	66.95
0.900	3413	498.7	324.1	11.94	170	67.06
1.000	3478	503.7	333.6	11.87	170	67.17
1.100	3554	511.8	346.4	11.89	170	67.30
1.200	3638	521.5	361.3	11.97	170	67.44
1.300	3725	530.6	376.4	12.07	170	67.56
1.400	3807	537.0	389.2	12.19	170	67.67
1.500	3877	539.9	398.5	12.29	170	67.75
1.600	3935	540.0	404.6	12.36	170	67.81
1.700	3982	539.1	408.7	12.43	170	67.85
1.800	4025	538.2	412.5	12.49	170	67.89
1.900	4067	537.7	416.4	12.54	170	67.92
2.000	4109	537.2	420.3	12.58	170	67.94
2.100	4151	536.4	423.9	12.58	170	67.96
2.200	4191	535.1	427.0	12.58	170	67.98
2.300	4231	533.6	429.8	12.57	170	67.99
2.400	4270	532.1	432.6	12.57	170	68.00
2.500	4308	530.7	435.3	12.59	170	68.00
2.600	4347	529.1	437.9	12.61	170	68.00
2.700	4387	527.5	440.6	12.61	170	67.98
2.800	4429	526.0	443.5	12.60	170	67.95
2.900	4473	525.0	447.1	12.59	170	67.92
3.000	4519	524.3	451.1	12.58	170	67.88
3.100	4566	523.5	455.1	12.57	170	67.85
3.200	4612	522.0	458.4	12.53	170	67.83
3.300	4656	519.8	460.8	12.49	170	67.83
3.400	4696	517.2	462.5	12.46	170	67.84
3.500	4735	514.9	464.2	12.46	170	67.86
3.600	4774	513.2	466.4	12.47	170	67.89
3.700	4813	512.0	469.2	12.47	170	67.91
3.800	4854	511.4	472.6	12.46	170	67.93
3.900	4899	511.0	476.6	12.47	170	67.94
4.000	4948	510.7	481.1	12.51	170	67.94
4.100	5001	510.4	486.0	12.55	170	67.95
4.200	5054	509.6	490.4	12.61	171	67.96
4.300	5107	508.1	494.0	12.63	171	67.97
4.400	5155	505.8	496.4	12.63	171	67.96
4.500	5198	502.8	497.6	12.65	171	67.94
4.600	5240	499.7	498.5	12.64	171	67.92
4.700	5280	496.9	499.6	12.64	171	67.89
4.800	5321	494.6	501.1	12.65	171	67.86
4.900	5366	492.4	503.1	12.65	171	67.84
5.000	5412	489.9	504.8	12.64	171	67.81
5.100	5460	486.9	506.2	12.60	171	67.77
5.200	5511	483.4	507.2	12.57	171	67.72
5.300	5562	479.5	507.8	12.55	171	67.66
5.400	5613	475.5	508.1	12.55	171	67.61
5.500	5663	471.4	508.3	12.56	171	67.55
5.600	5712	467.2	508.1	12.57	171	67.47
5.700	5757	462.9	507.4	12.58	171	67.37
5.800	5800	458.2	506.0	12.57	171	67.24
5.900	5839	453.1	503.8	12.57	171	67.11
6.000	5876	447.7	500.9	12.57	171	66.98
6.100	5912	442.1	497.7	12.56	171	66.87
6.200	5947	436.4	494.1	12.54	171	66.77
6.300	5981	430.3	490.0	12.49	171	66.68
6.400	6010	423.9	485.1	12.42	171	66.59
6.500	6032	418.2	480.3	12.33	171	66.51